DON'T WORRY, WE GOT YOU!



WRS6 Dual Defender

Class A

Average arresting force 1,350lbs

Maximum arrest distance 24"

Weight 5.14lbs

Dimension: (H)17.75", (W) 3.50", (D) 2"

Lifeline length: 6ft

3/4" UHMWPE & polyester webbing

Capacity: 130-310lbs or up to 420lbs

Lightweight nylon housing

Corrosion resistant internal

components

Shock absorber

Meets OSHA 1926.502,

OSHA 1910.66,

ANSI Z359.14,

CE EN 360:2002



FALL PROTECTION SYSTEMS AND TRAINING

With our lines of WRS Self Retracting Lifelines, you and your workers can have peace of mind and focus on your task at hand.

In the case of a fall, you can rest assured that our SRLs (properly used with a full body harness and an appropriate anchor point) will safely stop the fall.

Get the best SRL for your needs!

Whether you require shorter or longer lifeline, cable or webbing, leading edge, single or twin legs, we're sure to have the right SRL for you.

- Full scale SRL service and repair center
- Largest SRL inventory on the East Coast
- **SRL Rental Programs available**
- SRL's from 6' 120' in stock

Dual Defender w/ Rebar Hooks

ASR30

ASR30-RASS

\$220.00 min/10

\$225.00 min/10 \$240.00 min/10

Prices are good through the end of August.

ASR30

Class A

Average arresting force: 1,350lbs Maximum arrest distance: 24"

Lightweight design: 14.77lbs

Dimensions: (H)23.25", (W)8.25", (D)4.5"

Lifeline length: 30ft

3/16" dia. galvanized steel cable

Capacity: 130-310lbs or up to 420lbs Zinc plated hardware

Durable nylon housing

Corrosion resistant internal components.

Carry Handle

Meets or exceeds ANSI Z359.14-2012, OSHA 1926.502, OSHA 1910.66



ASR30-RASS

Class A

Average arresting force: 1,350lbs Maximum arrest distance: 24"

Lifeline length: 30ft

3/16" dia. galvanized steel cable

Capacity: 130-310lbs or up to 420lbs

Zinc plated hardware Nylon with fiber housing

Stainless steel inner components

Attachment point for secondary retention line

Meets or exceeds ANSI Z359.14-2012 A10,32-2012 OSHA 1926.502, 1910.66



